



RECOMMENDED MINIMUM HARDWARE DIAMETERS FOR SLINGMAX® TWIN-PATH® SLINGS – METRIC RATINGS 5:1 D.F.

Twin-Path® Sling Stock No.	VRC (Metric tonnes)	Minimum recommended hardware diameter (mm)	Minimum bending radius (mm)
TPXCVM5	5	16.00	8.00
TPXCVM10	10	25.40	12.70
TPXCVM15	15	35.05	17.53
TPXCVM20	20	35.56	17.78
TPXCVM25	25	38.10	19.05
TPXCVM30	30	38.10	19.05
TPXCVM35	35	45.72	22.86
TPXCVM40	40	45.72	22.86
TPXCVM50	50	53.09	26.55
TPXCVM60	60	63.50	31.75
TPXCVM70	70	71.12	35.56
TPXCVM85	85	71.12	35.56
TPXCVM100	100	76.20	38.10
TPXCVM115	115	76.20	38.10
TPXCVM130	130	93.98	46.99
TPXCVM150	150	93.98	46.99
TPXCVM170	170	119.89	59.95
TPXCVM200	200	119.89	59.95
TPXCVM225	225	130.30	65.15
TPXCVM250	250	130.30	65.15
TPXCVM275	275	139.70	69.85

Additional Twin-Path® sling information such as hitch capacities, approximate weights per foot and nominal body widths may be found in the Slingmax® catalog or at www.slingmax.com . Higher capacities are also available.

Dimensions are based on nominal bow width of Alloy shackles with comparable capacities. As alloys and other material grades vary among manufacturers it is the responsibility of the individual to ensure that capacities of rigging and hardware are compatible. If using a lower rated component part the sling should be used at the lower capacity of the fitting.