



RECOMMENDED MINIMUM HARDWARE DIAMETERS FOR SLINGMAX®

TWIN-PATH® SLINGS - 5:1 D.F.

Twin-Path® Sling Stock No.	VRC (Short tons)	Minimum recommended hardware diameter (in.)	Minimum bending radius (in.)
TPXCF/ TPXC1000	5	0.63	0.32
TPXCF/ TPXC1500	7.5	0.75	0.38
TPXCF/ TPXC2000	10	0.86	0.43
TPXCF/TPXC2500	12.5	1.00	0.50
TPXCF/ TPXC3000	15	1.10	0.55
TPXCF/ TPXC4000	20	1.40	0.70
TPXCF/TPXC5000	25	1.50	0.75
TPXCF/ TPXC6000	30	1.50	0.75
TPXCF/TPXC7000	35	1.84	0.92
TPXCF/ TPXC8500	42.5	1.84	0.92
TPXCF/ TPXC10000	50	2.00	1.00
TPXCF/ TPXC12500	62.5	2.50	1.25
TPXCF/ TPXC15000	75	2.50	1.25
TPXCF/ TPXC17500	87.5	2.80	1.40
TPXCF/ TPXC20000	100	3.00	1.50
TPXCF/ TPXC25000	125	3.30	1.65
TPXCF/ TPXC27500	137.5	3.62	1.81
TPXCF/ TPXC30000	150	3.62	1.81
TPXCF/ TPXC40000	200	4.70	2.35
TPXCF/ TPXC50000	250	5.10	2.55
TPXCF/ TPXC60000	300	5.50	2.75

Additional Twin-Path® sling information such as hitch capacities, approximate weights per foot and nominal body widths may be found in the Slingmax® catalog or at www.slingmax.com. Higher capacities and metric rated slings are also available.

Dimensions are based on nominal bow width of Alloy shackles with comparable capacities. As alloys and other material grades vary among manufacturers it is the responsibility of the individual to ensure that capacities of rigging and hardware are compatible. If using a lower rated component part the sling should be used at the lower capacity of the fitting.