

Technical Bulletin 58: Twin-Path® Roundsling Weight in Water Table

US Customary Units – 5:1 DF

Sling Size	Weight in lb/ft			Weight in kg/m		
	Air	Fresh Water	Seawater	Air	Fresh Water	Seawater
TPXCF 1,000	0.41	0.04	0.03	0.60	0.07	0.05
TPXCF 1,500	0.45	0.05	0.04	0.68	0.07	0.06
TPXCF 2,000	0.52	0.05	0.04	0.77	0.08	0.06
TPXCF 2,500	0.66	0.07	0.05	0.99	0.10	0.08
TPXCF 3,000	0.73	0.08	0.06	1.09	0.11	0.09
TPXCF 4,000	0.86	0.09	0.07	1.28	0.13	0.10
TPXCF 4,500	1.00	0.10	0.08	1.49	0.15	0.12
TPXCF 5,000	1.07	0.11	0.08	1.59	0.16	0.12
TPXCF 6,000	1.20	0.12	0.09	1.78	0.18	0.13
TPXCF 7,000	1.33	0.13	0.10	1.98	0.20	0.15
TPXCF 8,500	1.60	0.16	0.12	2.39	0.24	0.17
TPXCF 10,000	1.80	0.17	0.13	2.67	0.26	0.19
TPXCF 12,500	2.30	0.23	0.17	3.43	0.34	0.25
TPXCF 15,000	2.62	0.25	0.19	3.91	0.38	0.28
TPXCF 17,500	2.95	0.28	0.21	4.39	0.42	0.31
TPXCF 20,000	3.45	0.33	0.24	5.14	0.50	0.36
TPXCF 25,000	4.10	0.39	0.28	6.11	0.58	0.42
TPXCF 27,500	4.58	0.44	0.32	6.83	0.65	0.48
TPXCF 30,000	4.91	0.47	0.34	7.31	0.69	0.51
TPXCF 40,000	6.70	0.63	0.46	9.99	0.94	0.68
TPXCF 50,000	8.48	0.79	0.57	12.64	1.18	0.86
TPXCF 60,000	10.28	0.95	0.69	15.32	1.42	1.03

Note: All weights are calculated values and may vary. For critical applications, individual slings should be weighed before use.

Metric Units – 7:1 DF

Sling Size	Weight in lb/ft			Weight in kg/m		
	Air	Fresh Water	Seawater	Air	Fresh Water	Seawater
TPXC(F)M5	0.47	0.05	0.04	0.70	0.08	0.06
TPXC(F)M10	0.74	0.08	0.06	1.11	0.12	0.09
TPXC(F)M15	0.96	0.10	0.07	1.42	0.14	0.11
TPXC(F)M20	1.23	0.12	0.09	1.83	0.18	0.14
TPXC(F)M25	1.50	0.15	0.11	2.24	0.22	0.17
TPXC(F)M30	1.71	0.17	0.12	2.55	0.25	0.19
TPXC(F)M35	1.92	0.19	0.14	2.87	0.28	0.20
TPXC(F)M40	2.28	0.22	0.17	3.40	0.33	0.25
TPXC(F)M50	2.69	0.26	0.19	4.00	0.39	0.28
TPXC(F)M60	3.27	0.32	0.23	4.88	0.47	0.35
TPXC(F)M70	3.66	0.35	0.26	5.45	0.52	0.38
TPXC(F)M80	4.07	0.39	0.28	6.06	0.58	0.42
TPXC(F)M85	4.26	0.40	0.29	6.35	0.60	0.44
TPXC(F)M90	4.63	0.44	0.32	6.90	0.66	0.48
TPXC(F)M100	5.02	0.47	0.35	7.48	0.71	0.52
TPXC(F)M115	5.62	0.53	0.38	8.37	0.79	0.57
TPXC(F)M120	6.32	0.59	0.43	9.41	0.89	0.65
TPXC(F)M130	6.74	0.63	0.46	10.04	0.94	0.69
TPXC(F)M150	7.71	0.72	0.52	11.48	1.07	0.78
TPXC(F)M170	8.89	0.82	0.60	13.24	1.23	0.89
TPXC(F)M200	10.35	0.96	0.70	15.42	1.43	1.04

Note: All weights are calculated values and may vary. For critical applications, individual slings should be weighed before use.

Metric Units – 5:1 DF

Sling Size	Weight in lb/ft			Weight in kg/m		
	Air	Fresh Water	Seawater	Air	Fresh Water	Seawater
TPXC(F)MV5	0.41	0.04	0.03	0.60	0.07	0.05
TPXC(F)MV10	0.63	0.07	0.05	0.94	0.10	0.08
TPXC(F)MV15	0.78	0.08	0.06	1.16	0.12	0.09
TPXC(F)MV20	1.00	0.10	0.08	1.49	0.15	0.12
TPXC(F)MV25	1.15	0.12	0.09	1.71	0.17	0.13
TPXC(F)MV30	1.29	0.13	0.10	1.93	0.19	0.14
TPXC(F)MV35	1.44	0.14	0.10	2.15	0.21	0.16
TPXC(F)MV40	1.67	0.16	0.12	2.48	0.24	0.18
TPXC(F)MV50	1.96	0.19	0.14	2.92	0.28	0.21
TPXC(F)MV60	2.43	0.24	0.18	3.62	0.35	0.26
TPXC(F)MV70	2.72	0.26	0.19	4.05	0.39	0.29
TPXC(F)MV85	3.34	0.32	0.24	4.97	0.48	0.35
TPXC(F)MV100	3.77	0.36	0.26	5.62	0.54	0.39
TPXC(F)MV115	4.21	0.40	0.29	6.27	0.59	0.43
TPXC(F)MV130	4.81	0.46	0.33	7.16	0.68	0.50
TPXC(F)MV150	5.39	0.51	0.37	8.03	0.76	0.55
TPXC(F)MV170	5.97	0.56	0.41	8.90	0.83	0.61
TPXC(F)MV 200	7.38	0.69	0.50	11.00	1.02	0.75
TPXC(F)MV 225	8.45	0.79	0.57	12.59	1.17	0.85
TPXC(F)MV 250	9.23	0.85	0.62	13.75	1.27	0.92
TPXC(F)MV 275	10.35	0.96	0.70	15.42	1.43	1.04

Note: All weights are calculated values and may vary. For critical applications, individual slings should be weighed before use.