



**RECOMMENDED MINIMUM HARDWARE DIAMETERS FOR SLINGMAX®  
TWIN-PATH® SLINGS – METRIC RATINGS 5:1 D.F.**

*Dimensions are based on nominal bow width of a range of Alloy shackles with comparable capacities and are not intended to be all-inclusive. As alloys and other material grades vary among manufacturers it is the responsibility of the individual to ensure that capacities of rigging and hardware are compatible. If using a lower rated component part, the sling should be used at the lower capacity of the fitting.*

Twin-Path® Sling Stock No.	VRC (Metric tons)	Minimum recommended hardware diameter (mm)	Minimum bending radius (mm)
TPXCMV5	5	16.00	8.00
TPXCMV10	10	25.40	12.70
TPXCMV15	15	28.70	14.35
TPXCMV20	20	36.10	18.05
TPXCMV25	25	38.90	19.45
TPXCMV30	30	38.90	19.45
TPXCMV35	35	46.74	23.37
TPXCMV40	40	46.74	23.37
TPXCMV50	50	52.80	26.40
TPXCMV60	60	68.80	34.40
TPXCMV70	70	68.80	34.40
TPXCMV85	85	68.80	34.40
TPXCMV100	100	79.20	39.60
TPXCMV115	115	79.20	39.60
TPXCMV130	130	91.90	45.95
TPXCMV150	150	241.00	120.50
TPXCMV170	170	241.00	120.50
TPXCMV200	200	241.00	120.50
TPXCMV225	225	290.00	145.00
TPXCMV250	250	290.00	145.00
TPXCMV275	275	290.00	145.00
TPXCMV300	300	290.00	145.00
TPXCMV400	400	363.00	181.50

Additional Twin-Path® sling information such as hitch capacities, approximate weights per meter and nominal body widths may be found in the Slingmax® catalog or at [www.slingmax.com](http://www.slingmax.com) . Higher capacities and imperial rated slings are also available.