



**RECOMMENDED MINIMUM HARDWARE DIAMETERS FOR SLINGMAX®
TWIN-PATH® SLINGS – METRIC RATINGS 7:1 D.F.**

Dimensions are based on nominal bow width of a range of Alloy shackles with comparable capacities and are not intended to be all-inclusive. As alloys and other material grades vary among manufacturers it is the responsibility of the individual to ensure that capacities of rigging and hardware are compatible. If using a lower rated component part, the sling should be used at the lower capacity of the fitting.

Twin-Path® Sling Stock No.	VRC (Metric tons)	Minimum recommended hardware diameter (mm)	Minimum bending radius (mm)
TPXCM5	5	16.00	8.00
TPXCM10	10	25.40	12.70
TPXCM15	15	28.70	14.35
TPXCM20	20	36.10	18.05
TPXCM25	25	38.90	19.45
TPXCM30	30	38.90	19.45
TPXCM35	35	46.74	23.37
TPXCM40	40	46.74	23.37
TPXCM50	50	52.80	26.40
TPXCM60	60	68.80	34.40
TPXCM70	70	68.80	34.40
TPXCM85	85	68.80	34.40
TPXCM100	100	79.20	39.60
TPXCM115	115	79.20	39.60
TPXCM130	130	91.90	45.95
TPXCM150	150	241.00	120.50
TPXCM170	170	241.00	120.50
TPXCM200	200	241.00	120.50
TPXCM225	225	290.00	145.00
TPXCM250	250	290.00	145.00
TPXCM275	275	290.00	145.00
TPXCM300	300	290.00	145.00
TPXCM400	400	363.00	181.50

Additional Twin-Path® sling information such as hitch capacities, approximate weights per meter and nominal body widths may be found in the Slingmax® catalog or at www.slingmax.com. Higher capacities and imperial rated slings are also available.